

## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 4:

A63B 69/00

(11) International Publication Number:

WO 88/ 05323

(43) International Publication Date:

28 July 1988 (28.07.88)

(21) International Application Number:

PCT/US87/00218

**A1** 

(22) International Filing Date: 21 January 1987 (21.01.87)

(71) Applicant: PHILIPP, Harald [US/US]; 15320 NE 11th, Apartment K326, Bellevue, WA 98007 (US).

(74) Agent: FLICKINGER, Don, J.; 1700 North Seventh Street, Suite Three, Phoenix, AZ 85006 (US).

(81) Designated States: AT, AT (European patent), AU, BB, BE (European patent), BG, BR, CF (OAPI patent), CG (OAPI patent), CH, CH (European patent), CM (OAPI patent), DE, DE (European patent), DK, FI, FR (European patent), GA (OAPI patent), GB, GB (European patent), HU, IT (European patent), JP, KP, KR, LK, LU, LU (European patent), MC, MG, ML (OAPI patent), MR (OAPI patent), MW, NL, NL (European patent), NO, RO, SD, SE, SE (Eur patent), SN (OAPI patent), SU, TD (OAPI patent),

TG (OAPI patent).


**Published** 

With international search report.

(54) Title: ATHLETIC EVALUATION AND TRAINING APPARATUS

#### (57) Abstract

Apparatus and method for testing and enhancing the ability of a football player to quickly react to visual stimuli. When the player (X) leaves a starting position (10, 74), a first timer (48, 96) and a second timer (50, 98) begin counting in response to the breaking of a light beam (12, 76). When the player reaches a first reaction point (14, 80), the first counter is stopped thus containing an indication of how long it took for the player to reach the first reaction point. Simultaneously therewith, one of a battery of lights (20, 84), is energized indicating to the athlete that he must undertake and complete a particular action. This action may represent a cut right or cut left or may require the athlete to throw a ball at a particular target (86, 88, 90). The second timer is stopped when all the required actions have been completed thus giving an indication of how long it took the player to complete the entire course.



# FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

	• '				
AT	Austria	FR	France	ML.	Mali
AU	Australia	GA	Gabon		Mauritania
BB	Barbados	GB	United Kingdom	MW	Malawi
BE	Belgium	HU	Hungary	. NL	Netherlands
BG.	Bulgaria	n	Italy	NO	
BJ	Benin	JP	Japan		Norway
BR	Brazil	KP	•	RO	Romania
CF	Central African Republic	VI.	Democratic People's Republic	SD	Sudan
ĊĠ	Congo		of Korea	SE	Sweden
· CH		. KR	Republic of Korea	SN	Senegal
	Switzerland	LI	Liechtenstein	SU	Soviet Union
CM	Cameroon	LK	Sri Lanka	TD	Chad
DE	Germany, Federal Republic of	LU	Luxembourg	TG	Togo
DK	Denmark	MC	Monaco	US	United States of America
FI	Finland	.MG	Madagascar		or / interior

#### DESCRIPTION

# ATHLETIC EVALUATION AND TRAINING APPARATUS

5

10

25

30

#### Technical Field

This invention relates generally to the art of training athletes, and more particularly to an apparatus and method for electronically evaluating, under controlled conditions, an athlete's speed, agility, body control, and ability to react to visual stimuli.

#### Background Art

One of the major goals in training athletes, 15 especially football players, is develop to speed, coordination, lateral movement, peripheral vision, and ability to quickly change direction ("cut"). Typically, the forty yard dash is used to measure the speed of running backs, linemen, linebackers, defensive 20 · backs, etc. However, the forty yard dash is a flat out, straight ahead sprint which does not test the athlete's reaction time, peripheral vision, lateral movement or ability to cut.

Certain training aids have been developed. For States Patent example, United Nos. 3,534,958 4,029,315 disclose apparatus for testing a player's passing ability. U.S. Patent No. 3,096,979 discloses an agility developing device wherein one or more players respond to one or more moving targets. Unfortunately, such devices have very limited application and do not measure nor enhance the player's reaction time ability to quickly change direction in response to visual stimuli.

U.S. Patent No. 3,912,259 entitled APPARATUS FOR TIMED EVENTS PERFORMED BY CYCLISTS, issued October 14, 1975 discloses an obstacle course for timing events undertaken by cyclists. The cyclist initially proceeds over an actuator which starts a stopwatch, proceeds

around various objects or obstacles and eventually returns such that the entire event can be timed. The obstacles are painted either yellow or orange to indicate that the cyclist should pass to the right or left of the obstacle or marker. This arrangement does not provide, however, any means for redirecting the cyclist in another direction on a real-time basis and therefore does not test or improve his reaction time and ability to quickly respond to visual stimuli.

3

#### Disclosure Of The Invention

5

10

15

20

25

30

35

The present invention utilizes an obstacle course which involves different paths; e.g. to the right and left of a central path. A starting position is designated including an optical switch energized by a light beam. Upon a given command from the trainer or coach, the athlete begins his test by first running through the light beam. This causes the first optical switch to start two timers.

The athlete proceeds to a first reaction point which includes a second optical switch and light beam. When the second light beam is broken, the second optical switch causes the first timer to stop and further causes one of a battery of spaced apart lights which are located near the first reaction point to begin flashing. The direction in which the athlete is to proceed is indicated by which of the lights is flashing. For example, if the light on the right is flashing, the athlete must cut right. If the light on the left is flashing, the athlete must cut left. If the center light is flashing, the athlete must proceed in a straight ahead fashion.

The athlete proceeds in the direction indicated by the first battery of lights until he reaches a second reaction station whereupon he breaks a third light beam which is activating a third optical switch. Again, the direction in which the athlete is to proceed will be indicated by a flashing light. For example, depending on whether the right or left light is flashing, the athlete will know whether or not to cut around a selected one of two pylons.

Finally, the athlete proceeds to the finish line where he breaks a fourth light beam and triggers a fourth optical switch. This switch stops the second timer indicating how long it took the player to proceed through the entire course. To provide complete versatility, the same general types of paths and alternate routes are provided on the right and left sides of the central path

10

15

20

25

30

35

so that an athlete's ability to cut in either direction may be evaluated.

According to a broad aspect of the invention there is provided a method for testing and training an athlete, comprising measuring the length of time it takes the athlete to maneuver from a starting position to a first reaction point; and selecting one of a plurality of possible visual indications to be generated at the first reaction point to which the athlete must respond by undertaking and completing a pre-determined action.

According to a further aspect of the invention there is provided an apparatus for testing and training an athlete, comprising a first timer; first means coupled to the first timer for starting the first timer when the athlete leaves a starting position; second means coupled to the first timer for stopping the first timer when the athlete reaches a first reaction point; and third means for generating an indication at the first reaction point to which the player must respond by undertaking and completing a particular action.

### Disclosure of Invention

It is, therefore, an object of the present invention to provide an improved evaluation training device and method for training athletes.

It is a further object of the present invention to provide a testing and training device for athletes which will evaluate and develop the athlete's reaction time and ability to change direction in response to visual stimuli.

It is a still further object of the present invention to provide an improved evaluation and training device for athletes including an obstacle course, the nature of which can be electronically varied.

Another object of the present invention is to provide an athletic testing device and method including an obstacle course which may be easily controlled by the coach or trainer.

5

Yet another object of the present invention is to provide an improved evaluation device for football players which does not require contact with the player's body and thus minimizes the possibility of injury.

It is a further object of the present invention to provide an improved training device for football players which may be utilized to develop offensive, defensive and passing abilities.

Yet another object of the present invention is to provide an improved device and method for evaluating athletes, especially football players, which is radio controlled.

Another object of the present invention is to provide an evaluation and training device and method for training football players which utilizes an obstacle course having a plurality of electronically selectable paths.

It is a further object of the present invention to provide an improved training device and method for testing athletes such as football players which includes means for automatically recording the test results of the players.

### Brief Description of Drawings

5 .

10

15

20

35

25 foregoing and other objects, features advantages of the invention will be readily apparent from following description of certain preferred embodiments thereof, taken in conjunction with the accompanying drawings, although variations and 30 modifications may be affected without departing from the spirit and scope of the novel concept of the disclosure, and in which:

Figs. 1 and 2 illustrate first and second examples of the deployment of the inventive training device and how it is utilized to evaluate and train a player;

Fig. 3 is a legend identifying symbols used in Figs. 1 and 2 so as to assist in the explanation thereof;

6

Fig. 4 is a functional block diagram of the apparatus utilized in Fig. 1; and

Fig. 5 is a functional block diagram of the apparatus utilized in Fig. 2.

5

10

15

20

. 25

30

35

# Best Modes For Carrying Out Invention

Referring now to Figs. 1 and 3, athlete X begins the course at a starting point 10 by breaking a light beam 12. The breaking of light beam 12 causes an optical switch to start two timers as will be discussed in conjunction with Fig. 4. The athlete proceeds as quickly as possible to reaction point 14 as is indicated by arrow 16 at which point a second light beam 18 is broken. The breaking of this second light beam causes a second optical switch to cause one of the two timers to stop counting. In this manner, the athlete's speed from the starting point to the first reaction point 14 can be easily determined.

At reaction point 14, the athlete encounters a battery of lights 20. If the right light is flashing as is the case shown, the athlete should immediately cut right to pylon 22. At this point, a third light beam 24 is broken which activates a second battery of lights 26. If the left light is flashing as is the case shown, the athlete should cut left and proceed directly to pylon 28 at which a fourth light beam 30 is broken causing a fourth optical switch to stop the second counter. In this manner, the total time taken by the athlete to run the entire course may be determined.

Had the right light of light battery 26 been flashing instead of the left light, the athlete would have proceeded around pylon 32 as indicated by dotted arrows 34 prior to running to pylon 28. Similarly, if the center light of light battery 20 had been flashing when the athlete reached reaction point 14, the athlete would not cut right or left but would proceed straight ahead to pylon 28 as is indicated by dotted arrow 36. If the left light of light battery 20 had been flashing at

5

10

15

20

25

30

35

7

reaction point 14, the athlete would cut left toward pylon 38 and, depending on which light of light battery 40 was flashing, to either pylon 42 or pylon 28. Light beam 44 breaks if the athlete is proceeding around pylon 38 which causes an optical switch to energize either the right or left lights of light battery 40.

It is intended that the lights of light batteries 20, 26 and 40 be remotely controlled by the trainer or coach from the side lines so as to, in effect, customize the course being run by the athlete. This results in a test of the athlete's speed plus his ability to proceed, cut right or cut left in response to visual stimulus.

Fig. 4 is a block diagram of the apparatus utilized in Fig. 1. As stated previously, when the athlete starts the course, a light beam 12 is broken causing optical switch A 46 to generate a signal which is supplied to timers 48 and 50 causing them to start counting. the athlete reaches reaction point 14, an optical switch B 52 which is responsive to the breaking of light beam 18 causes timer 48 to stop counting. Thus, timer 48 contains a number indicative of the length of time it has taken the athlete to run from starting point 10 to reaction point 14. The output of optical switch B is applied to an And function 54 and is used to gate a control signal appearing on line 56 from control unit 58 through AND function 54 to light battery 20. case, the signal appearing on line 56 passes through AND function 54 and causes the right lamp of light battery 20 to flash.

When light beam 24 is broken, an optical switch C 60 is combined in AND function 62 with a signal appearing on line 64 from control unit 48. The coincidence of the breaking of light beam 24 and the presence of a control signal on line 64 causes the leftmost lamp of light battery 26 to flash. Optical switch D 66 is activated when light beam 44 is broken thus generating an output which is applied to an additional AND function 68 for controlling, along with a control line 70 from control

10

15

20

25

30

8

unit 58, which lamp of light battery 40 flashes. Finally, when light beam 30 is broken by the athlete passing pylon 28, regardless of the route taken by the athlete, an optical switch E 72 generates a signal which is applied to timer 50 to stop it. Thus, timer 50 contains a measurement indicative of the length of time taken by the athlete to run the entire course.

Control unit 58 may be a simple radio transmitter which is controlled by a plurality of two and three position toggle switches. The radio transmitter portion of control unit 58 would then generate signals for alterating the states of light batteries 20, 26, and 40. The toggle switches would enable the coach or trainer to pre-select a path through which the athletes are to proceed. A more sophisticated approach would be to have a control unit 58 comprised of a hand held computer and radio transmitter which would be operable for controlling the light batteries when the athlete breaks the light beams as described above. The hand held computer could be coupled to a printer for providing a printout of the results, including the athlete's name. Whether control unit 58 is a simple radio transmitter controlled by toggle switch or a microprocessor based computer system, is well within the capabilities of one skilled in the art to construct a control device for controlling the light batteries of the present invention.

Fig. 2 illustrates a second embodiment of the present invention which is particularly useful in the training and evaluation of quarterbacks. In this case, the player or quarterback 74 begins the test by moving backwards with a football in hand breaking the light beam 76. This causes first and second timers to begin counting. The quarterback continues moving backwards in the direction of arrows 78 until he reaches reaction point 80 and breaks a second light beam 82. The breaking of light beam 82 causes two things to happen. First, a signal is generated stopping the first timer giving an indication of the length of time it takes the quarterback

5

10

15

20

25

30

35

q

to back-peddle from the starting point to the first reaction point 80. Second, one of the left, center or right lamps of light battery 84 is caused to begin flashing. The flashing lamp indicates to the quarterback which one of three targets 86, 88 or 90 he is to throw the football at. That is, if the right lamp is flashing the quarterback must throw the football at target 90. the center lamp is flashing, the quarterback must throw the football at target 88. In the case shown in Fig. 2, the left lamp is flashing indicating to the quarterback that he must throw the football at target 86 as is indicated by arrows 92. If the football strikes the target, a switch coupled to the target causes a second timer to stop thus giving an indication as to the total length of time required for that quarterback to receive a snap and hit the appropriate target.

Fig. 5 is a functional block diagram illustrating apparatus which would function to produce the course shown in Fig. 2. Upon breaking of light beam 76, optical switch A 94 generates a signal which causes timers 96 and 98 to begin counting. When the quarterback has backed up to reaction point 80, light beam 82 is broken which causes an optical switch B 100 to generate a signal which stops timer 96. This signal is also applied to an AND function 102 as is a signal from control unit 104. output of AND function 102 is applied to light battery 84 and lights an appropriate one of the three lamps, in this case the last one. Each of the targets 86, 88 and 90 is coupled to an impact switch 106, 108 and respectively. When the football strikes the appropriate target, the appropriate switch will cause a signal to be applied via OR gate 112 to timer 98 in order to stop it. Thus, timer 98 will contain a measurement indicative of the length of time it took the quarterback to receive the snap and strike the appropriate target.

Thus the inventive training technique described above provides an obstacle course the nature of which may

be varied in real time so as to test a player's ability to respond to visual stimuli.

The above description is given by way of example only. Changes in form and details may be made by one skilled in the art without departing from the scope of the invention as defined by the appended claims.

## Industrial Applicability

The instant invention provides that an athlete can practice or be performance evaluated in an environment simulating a team competition sport, such as football. Under the controlled conditions selectively established by the invention, training can be intensified and performance more critically reviewed. The apparatus and method are conveniently usable by an individual player or by a coach. The device is readily fabricated of known materials and using techniques of the trade as will be appreciated by those skilled in the art.

20

5

25

30

5

10

15

20

### 11 CLAIMS

1. A method for testing and training an athlete, comprising:

measuring the length of time it takes the athlete to maneuver from a starting position to a first reaction point; and

selecting one of a plurality of possible visual indications to be generated at said first reaction point to which the athlete must respond by undertaking and completing a pre-determined action.

2. A method according to Claim 1, wherein said plurality of possible visual indications includes the energizing of one of a plurality of lamps, the position of which indicates the action to be taken.

- 3. A method according to Claim 1, further including measuring the length of time it takes the athlete to complete the pre-determined action after leaving said starting position.
- 4. A method according to Claim 3, wherein said particular action is a cut right.

- 5. A method according to Claim 3, wherein said particular action is a cut left.
- 6. A method according to Claim 3, wherein said particular action comprises throwing a ball at a particular target.
- 7. An apparatus for testing and training an athlete, comprising:

#### a first timer;

first means coupled to said first timer for starting said first timer when said athlete leaves a starting position;

second means coupled to said first timer for stopping said first timer when said athlete reaches a first reaction point; and \_\_

third means for generating an indication at said first reaction point to which the player must respond by undertaking and completing a particular action.

10

5

15

5

10

20

8. An apparatus according to Claim 7, further comprising:

a second timer coupled to said first means and started thereby; and

fourth means coupled to said second timer for stopping said second timer when the athlete has completed said pre-determined action.

- 9. An apparatus according to Claim 8, further comprising remote control means for controlling said third means.
  - 10. An apparatus according to Claim 9, wherein said first, second an fourth means are optical means.
- 11. An apparatus according to Claim 10, wherein each of said optical means comprises:

a light source; and

an optical switch responsive to an interruption in said light source.

12. An apparatus according to Claim 9, wherein said indication is a visual indication.

13. An apparatus according to Claim 12, wherein said visual indication comprises the energization of a particular one of a plurality of lamps.

BEST AVAILABLE COPY PCT/US87/00218 WO 88/05323 1/2 16

# BEST AVAILABLE COPY

WO 88/05323 PCT/US87/00218 2/2 X ATHLETE REACTION POINT **PYLON** PATH OF ATHLETE **TARGET** PATH OF BALL OD LIGHTS LIGHT BEAM ·IGO *58*) (46 48) 527 STOP START **OPTICAL** OPTICAL CONTROL **TIMER** SWITCH A SWITCH B *5*6 (54 *50*) 64) **OPTICAL** TIMER SWITCH C 60 J 70 **OPTICAL** SWITCH D 66J STOP **OPTICAL** FIGA SWITCH E 72] 104 (94 96) (100 STOP OPTITAL **OPTICAL** START TIMER CONTROL SWITCH B SWITCH A 98 **TIMER** 106) **SWITCH** 

108

110)

**SWITCH** 

**SWITCH** 

112

STOP

## INTERNATIONAL SEARCH REPORT

	International Application No PCT/US87/00218									
I. CLASSIFICATION OF SUBJECT MATTER (If several classification symbols apply, indicate all) 3										
According to International Patent Classification (IPC) or to both National Classification and IPC IPC (4): A63B 69/00										
U.S. Cl: 434/251										
II. FIELDS SEARCHED										
Minimum Documentation Searched +										
Classification System   Classification Symbols										
U.S.	U.S. 434/247,251,255 272/100									
Documentation Searched other than Minimum Documentation to the Extent that such Documents are included in the Fields Searched •										
III. DOCUMENTS CONSIDERED TO BE RELEVANT "										
Category •	Citat	ion of Document, 16 with Indication, where app	ropriate, of the relevant passages LT	Relevant to Claim No. 16						
A	US, A, 3,846,704 (BESSETTE) 05 NOVEMBER 1974, See entire document									
A	US,A 2	1-13								
			·							
l										
ĺ										
		_								
:		•								
		•								
ļ										
1										
j										
				he international filing date						
		s of cited documents: 15 ning the general state of the art which is not	"T" later document published after or priority date and not in conflicted to understand the princip							
cons	sidered to I	be of particular relevance	invention							
filing	g date	nt but published on or after the international	"X" document of particular relevant cannot be considered novel of	r cannot be considered to						
"L" document which may throw doubts on priority claim(s) or involve an inventive step  which is cited to establish the publication date of another which is cited to establish the publication date of another which is cited to establish the publication date of another which is cited to establish the publication date of another which is cited to establish the publication date of another which is cited to establish the publication date of another which is cited to establish the publication date of another which is cited to establish the publication date of another which is cited to establish the publication date of another which is cited to establish the publication date of another which is cited to establish the publication date of another which is cited to establish the publication date of another which is cited to establish the publication date of another which is cited to establish the publication date of another which is cited to establish the publication date of another which is cited to establish the publication date of another which is cited to establish the publication date of another which is cited to establish the publication date of another which is cited to establish the publication date of another which is cited to establish the cited to establish the publication date of another which is cited to establish the cited to estab										
	cannot be considered to involve an inventve step when the									
other means ments, such combination being obvious to a person same										
"P" document published prior to the international filing date but later than the priority date claimed "&" document member of the same patent family										
IV. CERTIFICATION										
Date of the Actual Completion of the International Search 2 2 7 APRIL 1987										
International Searching Authority 1  ISA/US  L. Picard  Isa/US										
ISA/U	IS		L. Picard	· · · · · · · · · · · · · · · · · · ·						